



Catalogue  
**PORTABLE GANTRY CRANE**



UP TO NOW, WE EXPORT MORE THAN **50** COUNTRIES

**HEHAN ZOKE CRANE CO., LTD**

EMAIL: [sales@zokecrane.com](mailto:sales@zokecrane.com)

TEL: +86 373-3872-232

FAX: +86 373-5259-699

WEB: [www.zoke-crane.com](http://www.zoke-crane.com)

[www.zokecrane.com](http://www.zokecrane.com)

ADDRESS: Changnao Industrial District, Xinxiang, Henan China

**HEHAN ZOKE CRANE CO., LTD**

[www.zokecrane.com](http://www.zokecrane.com)

# ABOUT ZOKECRANE

## Quality Is Our Top Priority

ZOKE CRANE is ISO9001-2008 registered. This means we actively monitor every part of our business, conducting monthly evaluations that cover everything from customer service to delivery times.

## Technical Innovation Is Our Development Concept

ZOKE CRANE has been constantly carrying out technological innovation for many years, communicating and cooperating with internationally renowned enterprises, actively introducing high-tech, and pushing the ZOKE brand to the international market. Develop new products to meet the market demand for high-end products, market-oriented, based on integrity, take the road of technological innovation.

## Service Is The Basis Of Our Survival

It is our aim to improve the production efficiency of customers. Customized and OEM accepted We provide professional consultant, sales, design, production, installation and commissioning, maintenance for customers worldwide.



# CONTENT



**Fixed Height Gantry Crane..... 01**

Motorized Travel Type ..... 01

Hand Push Type ..... 03



**Adjustable Height Gantry Crane..... 05**

Hand Winch Type ..... 05

Worm Type ..... 07

Motorized Type ..... 09



**Aluminum Gantry Crane..... 11**

Feature of LT-1 Type Crane ..... 11

Feature of LT-2 Type Crane ..... 13

Feature of LT-3 Type Crane ..... 15



# Fixed Height Gantry Crane

## Motorized Travel Type



### Feature

- Fixed height, the lift height is not adjustable.
- Crane long traveling driven by MOTOR.
- Two motorized wheel and two universal castor with brake device
- Easy installation and maintenance

### Parameters

Capacity (t)	Total Height (mm)	Lift Height (mm)	Total Width (mm)	Inner Width (mm)	Lift Speed (m/min)	Cross Travel Speed (m/min)	Long Travel Speed (m/min)
1	3000	2390	3000	2760	6.6	10	6
1	4000	3390	4000	3760	6.6	10	6
1	5000	4390	4000	3760	6.6	10	6
1	5000	4340	5000	4760	6.6	10	6
2	3000	2215	3000	2720	6.6	10	6
2	4000	3215	4000	3720	6.6	10	6
2	5000	4215	4000	3720	6.6	10	6
2	5000	4215	5000	4720	6.6	10	6
3	3000	2015	3000	2660	5.4	10	6
3	4000	3015	4000	3660	5.4	10	6
3	5000	4015	4000	3660	5.4	10	6
3	5000	4015	5000	4660	5.4	10	6
5	3000	1910	3000	2560	2.7	10	6
5	4000	2910	4000	3560	2.7	10	6
5	5000	3910	4000	3560	2.7	10	6
5	5000	3910	5000	4560	2.7	10	6

Note: 1. The Customized Service Is Provided.  
 2. Hoist Option: Electric Hoist Or Manual Chain Block.

### Products Show



# Fixed Height Gantry Crane

## Hand Push Type



### Feature

- Fixed Height, The Lift Height Is Not Adjustable.
- Crane Long Traveling Driven By Manual Power.
- Four Universal Castor With Brake Device
- Easy Installation And Maintenance

### Parameters

Capacity (t)	Total Height (mm)	Lift Height (mm)	Total Width (mm)	Inner Width (mm)	Lift Speed (m/min)	Cross Travel Speed (m/min)	Long Travel Speed (m/min)
1	3000	2390	3000	2760	6.6	10	manual
1	4000	3390	4000	3760	6.6	10	manual
1	5000	4390	4000	3760	6.6	10	manual
1	5000	4340	5000	4760	6.6	10	manual
2	3000	2215	3000	2720	6.6	10	manual
2	4000	3215	4000	3720	6.6	10	manual
2	5000	4215	4000	3720	6.6	10	manual
2	5000	4215	5000	4720	6.6	10	manual
3	3000	2015	3000	2660	5.4	10	manual
3	4000	3015	4000	3660	5.4	10	manual
3	5000	4015	4000	3660	5.4	10	manual
3	5000	4015	5000	4660	5.4	10	manual
5	3000	1910	3000	2560	2.7	10	manual
5	4000	2910	4000	3560	2.7	10	manual
5	5000	3910	4000	3560	2.7	10	manual
5	5000	3910	5000	4560	2.7	10	manual

Note: 1. The Customized Service Is Provided.  
 2. Hoist Option: Electric Hoist Or Manual Chain Block.  
 3. Long Traveling Way: Manual Push.

### Products Show



# Adjustable Height Gantry Crane

## Hand Winch Type



### Feature

- The Lift Height And Total Height Of Crane Is Adjustable, According To Your Requirement.
- Turn Hand Winch Adjust The Height, Pin Shaft To Fix The Height And Bear The Weight.
- Crane Long Traveling Can Be Driven By Manual Power Or Motor.

### Parameters

Capacity (t)	Total Height (mm)	Lift Height (mm)	Total Width (mm)	Inner Width (mm)	Lift Speed (m/min)	Cross Travel Speed (m/min)	Long Travel Speed (m/min)
1	2600-4000	3390	3000	2760	6.6	10	6
1	3000-4500	3890	3000	2760	6.6	10	6
1	4000-6000	5390	3000	2760	6.6	10	6
2	2600-4000	3215	3000	2690	6.6	10	6
2	3000-4500	3715	3000	2690	6.6	10	6
2	4000-6000	5215	3000	2690	6.6	10	6
3	2600-4000	3015	3000	2690	5.4	10	6
3	3000-4500	3515	3000	2690	5.4	10	6
3	4000-6000	5015	3000	2690	5.4	10	6
5	2600-4000	2910	3000	2610	2.7	10	6
5	3000-4500	3410	3000	2610	2.7	10	6
5	4000-6000	4910	3000	2610	2.7	10	6

Note: 1. The Customized Service Is Provided.

2. Hoist Option: Electric Hoist Or Manual Chain Block.

3. Long Traveling Way: Manual Push.

### Products Show



# Adjustable Height Gantry Crane

Worm Type



## Feature

- The Lift Height And Total Height Of Crane Is Adjustable, According To Your Requirement.
- Turn The Worm To Slowly Adjust The Height And Make The Fine-tuning.
- Crane Long Traveling Can Be Driven By Manual Power Or Motor.

## Parameters

Capacity (t)	Total Height (mm)	Lift Height (mm)	Total Width (mm)	Inner Width (mm)	Lift Speed (m/min)	Cross Travel Speed (m/min)	Long Travel Speed (m/min)
1	2600-4000	3390	3000	2760	6.6	10	6
1	3500-5000	4390	3000	2760	6.6	10	6
2	2600-4000	3215	3000	2690	6.6	10	6
2	3500-5000	4215	3000	2690	6.6	10	6
3	2600-4000	3015	3000	2690	5.4	10	6
3	3500-5000	4015	3000	2690	5.4	10	6
5	2600-4000	2910	3000	2610	2.7	10	6
5	3500-5000	3910	3000	2610	2.7	10	6

Note: 1. The Customized Service Is Provided.  
 2. Hoist Option: Electric Hoist Or Manual Chain Block.  
 3. Long Traveling Way: Manual Push.

## Products Show





# Adjustable Height Gantry Crane

Motorized Type



## Feature

- The Lift Height And Total Height Of Crane Is Adjustable, According To Your Requirement.
- Motor Drive To Adjust The Height, More Easy And High Work Efficiency.
- Crane Long Traveling Can Be Driven By Manual Power Or Motor.

## Parameters

Capacity (t)	Total Height (mm)	Lift Height (mm)	Total Width (mm)	Inner Width (mm)	Lift Speed (m/min)	Cross Travel Speed (m/min)	Long Travel Speed (m/min)
1	2600-4000	3390	3000	2760	6.6	10	6
1	3000-4500	3890	3000	2760	6.6	10	6
1	4000-6000	5390	3000	2760	6.6	10	6
2	2600-4000	3215	3000	2690	6.6	10	6
2	3000-4500	3715	3000	2690	6.6	10	6
2	4000-6000	5215	3000	2690	6.6	10	6
3	2600-4000	3015	3000	2690	5.4	10	6
3	3000-4500	3515	3000	2690	5.4	10	6
3	4000-6000	5015	3000	2690	5.4	10	6
5	2600-4000	2910	3000	2610	2.7	10	6
5	3000-4500	3410	3000	2610	2.7	10	6
5	4000-6000	4910	3000	2610	2.7	10	6

Note: 1.The Customized Service Is Provided.

2. Hoist Option: Electric Hoist Or Manual Chain Block

3. Long Traveling Option: Manual Push Or Motorized Drive

## Products Show



# Aluminum Gantry Crane

## Feature of LT-1 Type Crane

The aluminum gantry crane is suitable for places with high cleanliness, high corrosion resistance, high explosion resistance, and limited floor bearing capacity (laboratory, high buildings, food processing plants, etc.). The biggest advantage is easy to deliver from one place to another place. Easy installation and strong portability.

The current styles are LT1, LT2, LT3.

### Feature of LT-1 Type Crane

- Fixed Lift Height And Total Height
- Adjustable Working Width
- Long Travel: Hand Push
- Hoist Model: Manual Chain Block



### LT-1 Parameters

Capacity (t)	Total Height (mm)	Max Lift Height (mm)	Total Width (mm)	Inner Width (mm)
0.5	3000	2420	2000	1880
0.5	3000	2420	3000	2880
0.5	4000	3420	3000	2880
1	3000	2470	2000	1880
1	3000	2470	3000	2880
1	4000	3470	3000	2880
2	3000	2215	2000	1800
2	3000	2215	3000	2800
2	4000	3215	3000	2800
3	3000	2122	2000	1800
3	3000	2122	3000	2800
3	4000	3122	3000	2800

### Products Show





# Aluminum Gantry Crane

## Feature of LT-2 Type Crane

The aluminum gantry crane is suitable for places with high cleanliness, high corrosion resistance, high explosion resistance, and limited floor bearing capacity (laboratory, high buildings, food processing plants, etc.). The biggest advantage is easy to deliver from one place to another place. Easy installation and strong portability.

The current styles are LT1, LT2, LT3.

## Feature of LT-1 Type Crane

- Adjustable Lift Height And Total Height
- Adjustable Working Width
- Long Travel: Hand Push
- Hoist Model: Manual Chain Block



## LT-1 Parameters

Capacity (t)	Total Height (mm)	Max Lift Height (mm)	Total Width (mm)	Inner Width (mm)
1	2000-3000	2470	3000	2880
1	2000-3000	2470	4000	3880
1	2600-4000	3470	3000	2880
2	2000-3000	2215	3000	2800
2	2000-3000	2215	4000	3800
2	2600-4000	3315	3000	2800
3	2000-3000	2122	3000	2800
3	2000-3000	2122	4000	3800
3	2600-4000	3122	3000	2800

## Products Show



## Aluminum Gantry Crane

### Feature of LT-3 Type Crane

The aluminum gantry crane is suitable for places with high cleanliness, high corrosion resistance, high explosion resistance, and limited floor bearing capacity (laboratory, high buildings, food processing plants, etc.). The biggest advantage is easy to deliver from one place to another place. Easy installation and strong portability.

The current styles are LT1, LT2, LT3.

### Feature of LT-1 Type Crane

- Adjustable Lift Height And Total Height
- Adjustable Working Width
- Long Travel: Fixed
- Hoist Model: Manual Chain Block



### LT-1 Parameters

Capacity (t)	Total Height (mm)	Max Lift Height (mm)	Total Width (mm)	Inner Width (mm)
1	2000-3000	2470	3000	2880
1	2000-3000	2470	4000	3880
1	2600-4000	3470	3000	2880
2	2000-3000	2215	3000	2800
2	2000-3000	2215	4000	3800
2	2600-4000	3315	3000	2800
3	2000-3000	2122	3000	2800
3	2000-3000	2122	4000	3800
3	2600-4000	3122	3000	2800

### Products Show

